

1. Unique identification code of the product-type:

## Tytan Professional FIX2 TURBO GT MOUNTING ADHESIVE



2. **Type, batch or serial number** or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. **Intended use or uses** of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

### EN 15651-1:2012 Type F-EXT-INT Class 7,5P

non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face.

### EN 15651-3:2012 Type S Class S 1

sealant used for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water

It covers joints in:

- bathrooms;
- toilets;
- showers;
- domestic kitchens.

4. Name, registered trade name or registered trade mark and contact address of the **manufacturer** as required pursuant to Article 11(5):

SELENA FM S.A.  
Legnicka 48A  
54-202 Wrocław  
Poland

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. **System or systems of assessment** and verification of constancy of performance of the construction product as set out in Annex V:

system 3 for type of testing  
system 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a **harmonised standard**:

The notified body Tecnia, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

The notified body Tecnia, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a **European Technical Assessment** has been issued:

not relevant

9. Declared performance

### EN 15651-1:2012 Type F-EXT-INT

Conditioning: Method A

Substrate: anodised aluminium without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-1:2012
Water tightness and air tightness:			
Resistance to flow	≤ 3 mm	modified EN ISO 7390	EN 15651-1:2012
Loss of volume	≤ 25%	EN ISO 10563	EN 15651-1:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 25%	EN ISO 10591	EN 15651-1:2012
Tensile properties (i.e. elongation): - at maintained extension after water immersion	NPD	EN ISO 10590	EN 15651-1:2012
Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	NPD	modified EN ISO 8339	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): - for non-structural sealants used in joints in cold climate areas (-30°C)	NPD	modified EN ISO 8340	EN 15651-1:2012
Durability	Pass	EN ISO 8339, EN ISO 10591, EN ISO 9046	EN 15651-1:2012

## EN 15651-3:2012 Type S

Conditioning: Method A

Substrate: anodised aluminium without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-3:2012
Water tightness and air tightness:			
Resistance to flow	≤ 5 mm	modified EN ISO 7390	EN 15651-3:2012
Loss of volume	≤ 55%	EN ISO 10563	EN 15651-3:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 25%	EN ISO 10591	EN 15651-3:2012
Tensile properties (i.e. elongation): - at maintained extension after water immersion	NPD	EN ISO 10590	EN 15651-3:2012
Microbiological growth	0 +	EN ISO 846:1997, procedure B	EN 15651-3:2012

Durability	Pass	EN ISO 846, EN ISO 8339, EN ISO 10591, EN ISO 9046	EN 15651-3:2012
------------	------	--	-----------------

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the  
manufacturer by:

Ewa Topór  
(R&D Certification Coordinator)



23.04.2024, Wrocław

#### Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance