

DECLARATION OF PERFORMANCE



Page: 1 according Annex III of the Regulation (EU) No 305/2011 0000000418 Edition: 26.04.2024

1. Unique identification code of the product-type:

Tytan Professional FIX2 CLEAR ADHESIVE-SEALANT



 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): batch number: see packaging of the product

 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 15651-1:2012 Type F-EXT-INT Class 7,5P

non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face.

EN 15651-3:2012 Type S Class S 1

sealant used for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water

 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): SELENA FM S.A. Legnicka 48A 54-202 Wrocław Poland

- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

system 3 for type of testing system 3 for the reaction to fire

 In case of the declaration of performance concerning a construction product covered by a harmonised standard: The notified body Tecnalia, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

The notified body Tecnalia, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: classification report

 In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

EN 15651-1:2012 Type F-EXT-INT

Conditioning: Method A Substrate: glass without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501- 1:2007+A1	EN 15651-1:2012



DECLARATION OF PERFORMANCE



Page: 2

according Annex III of the Regulation (EU) No 305/2011 0000000418 Edition: 26.04.2024

Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-1:2012
Water tightness and air tightness:			
Resistance to flow	≤ 3mm	modified EN ISO 7390	EN 15651-1:2012
Loss of volume	≤ 25%	EN ISO 10563	EN 15651-1:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 25%	EN ISO 10591	EN 15651-1:2012
Tensile properties (i.e. elongation): -at maintained extension after water immersion	NPD	EN ISO 10590	EN 15651-1:2012
Tensile properties (i.e. secant modulus): -for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	NPD	modified EN ISO 8339	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): -for non-structural sealants used in joints in cold climate areas (-30°C)	NPD	modified EN ISO 8340	EN 15651-1:2012
Durability	Pass	EN ISO 8339, EN ISO 9046, EN ISO 10591	EN 15651-1:2012

EN 15651-3:2012 Type **S** Conditioning: Method A Substrate: glass without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501- 1:2007+A1	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-3:2012
Water tightness and air tightness:			
Resistance to flow	≤ 5mm	modified EN ISO 7390	EN 15651-3:2012
Loss of volume	≤ 55%	EN ISO 10563	EN 15651-3:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 25%	EN ISO 10591	EN 15651-3:2012
Tensile properties (i.e. elongation): - at maintained extension after water immersion	NPD	EN ISO 10590	EN 15651-3:2012
Microbiological growth	1	EN ISO 846:1997, procedure B	EN 15651-3:2012
Durability	Pass	EN ISO 10591, EN ISO 846	EN 15651-3:2012



DECLARATION OF PERFORMANCE



Page: 3 according Annex III of the Regulation (EU) No 305/2011 0000000418 Edition: 26.04.2024

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Ewa Topór (R&D Certification Coordinator)

26.04.2024, Wrocław

Annex

According to Art. 6 (5) of the Regulaton (EU) No. 305/2011 a Safety Data sheet according Regulation (EU)No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance