

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Tytan Professional IS73 SILICONE FACADE PAINT
- **Article number:** D-3270
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
TP
Selena FM S.A.
ul. Strzegomska 2-4, 53-611 Wrocław, Poland
tel.: +48 71 78 38 290, fax: +48 71 78 38 291
e-mail: office@selenafm.com
www.selenafm.com
BDO: 000136566
- **Further information obtainable from:** msds@selenafm.com
- **1.4 Emergency telephone number:** European emergency number: 112 (24h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements**
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P102 Keep out of reach of children.
P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH208 Contains a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1), 2-octyl-2H-isothiazol-3-one, 4,5-dichloro-2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
Contains biocidal products: a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 1)

• Dangerous components:

CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<0.05%
CAS: 886-50-0 EINECS: 212-950-5	terbutryn ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317	<0.1%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.0015%
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.0015%
CAS: 64359-81-5	4,5-dichloro-2-octyl-2H-isothiazol-3-one ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.025 % Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.0015%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately rinse with water.

DO NOT use solvents or thinners.

If skin irritation continues, consult a doctor.

• After eye contact:

If present, remove contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 2)

- **After swallowing:**
Rinse out mouth with water.
Do not induce vomiting.
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
Contact with eyes: May cause irritation, pain and redness of the eyes.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fire with alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet.
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon dioxide (CO₂).
Carbon monoxide (CO).
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Refer to section 8.
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers / surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
At work do not eat, drink or smoke.
Avoid contact with respiratory system, skin and eyes. See also section 8.
Ensure good ventilation / exhaust at the workplace.
- **Information about fire - and explosion protection:** No special measures required.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**
 - Store away from water.
 - Do not store together with alkalis (caustic solutions).
 - Do not store together with acids.
- **Further information about storage conditions:**
 - Protect from frost.
 - Protect from humidity and water.
 - Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 13463-67-7 titanium dioxide

WEL	Long-term value: 10* 4** mg/m ³
	*total inhalable **respirable

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
 - The usual precautionary measures are to be adhered to when handling chemicals.
 - Do not inhale dust / smoke / mist.
 - Do not eat, drink, smoke or sniff while working.
 - Keep away from foodstuffs, beverages and feed.
 - Avoid contact with the eyes and skin.
 - Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.020 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Short term contact: ≥ 10 min (EN 374)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Safety glasses

EN 166

• Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

• General Information

• Physical state	Fluid
• Colour:	According to product specification
• Odour:	Weak, characteristic
• Odour threshold:	Not determined
• Melting point/freezing point:	Not determined
• Boiling point or initial boiling point and boiling range	Not determined
• Flammability	Not applicable
• Lower and upper explosion limit	
• Lower:	Not determined
• Upper:	Not determined
• Flash point:	Not applicable
• Auto-ignition temperature:	Product is not selfigniting
• Decomposition temperature:	Not determined
• pH	8-9
• Viscosity:	
• Kinematic viscosity	Not determined
• Dynamic:	Not determined
• Solubility	
• water:	Fully miscible
• Partition coefficient n-octanol/water (log value)	Not determined
• Vapour pressure:	Not determined
• Density and/or relative density	
• Density at 20 °C:	1.50 g/cm ³
• Relative density	Not determined
• Vapour density	Not determined

• 9.2 Other information

• Appearance:

• Form: Fluid

• Important information on protection of health and environment, and on safety.

• Explosive properties: Product does not present an explosion hazard

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 5)

· Change in condition	
· Evaporation rate	Not determined
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid**
Avoid humidity.
Avoid direct sunlight, sources of heat and fire.
Protect from frost.
- **10.5 Incompatible materials:** Strong acids, alkalis and oxidising agents.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

Oral	LD50	49-75 mg/kg (rat)
Dermal	LD50	141 mg/kg (rabbit)
Inhalative	LC50/4h	0.33 mg/l (rat)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 6)

CAS: 64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one

Oral	LD50	3,300 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>5,000 mg/kg (rat)
--------	------	--------------------

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

CAS: 556-67-2	Octamethylcyclotetrasiloxane, D4
---------------	----------------------------------

List II; III

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50	4.5 mg/l (bacteria)
	0.16 mg/l (daphnia) (48h)
LC50	0.018 mg/l (algae) (72h)
	0.19 mg/l (fish) (96h)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Dispose of in a safe manner in accordance with local / national regulations.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 7)

Do not allow to enter surface or ground water.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

Substance/mixture as a waste compound brings hazardous properties HP: 14

• European waste catalogue

15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP14	Ecotoxic

• Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

• **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

• 14.1 UN number or ID number

• ADR, IMDG, IATA Not applicable

• 14.2 UN proper shipping name

• ADR, IMDG, IATA Not applicable

• 14.3 Transport hazard class(es)

• ADR, ADN, IMDG, IATA

• Class Not applicable

• 14.4 Packing group

• ADR, IMDG, IATA Not applicable

• 14.5 Environmental hazards:

Not applicable.

• 14.6 Special precautions for user

Not applicable.

• 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

• UN "Model Regulation":

Not applicable

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, REACH

1272/2008/CE Regulation, CLP

2020/878/UE Regulation

• Directive 2012/18/EU

• **Named dangerous substances - ANNEX I** None of the ingredients is listed.

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

(Contd. of page 8)

• REGULATION (EU) 2019/1148

• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

• Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

• Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

• Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• Other regulations, limitations and prohibitive regulations No restriction

• Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

• Version number of previous version: 1

• Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 2: Acute toxicity – Category 2
- Skin Corr. 1: Skin corrosion/irritation – Category 1
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A

(Contd. on page 10)



Page 10/10

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.03.2022

Version number 2 (replaces version 1)

Revision: 10.03.2022

Trade name: Tytan Professional IS73 SILICONE FACADE PAINT

Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 9)

—GB—