

TYTAN PROFESSIONAL Acrylic Rapid Filler

Rapid acrylic filler recommended for filling scratches and cracks on walls and ceilings as well as masking the heads of screws and fasteners used in installing partition walls and suspended ceilings. Walls can be painted after 20 minutes.



BENEFITS

- The product is a lightweight filler easy to apply thanks to its good extrusion properties.
- It dries quickly, does not shrink, nor crack once dry.
- It can be used indoor and outdoor.

RECOMMENDED USES

- Specially recommended to repair and fill cracks, holes, fissures, etc., in wood surrounds, plasters or cement and in general, any kind of porous construction materials.
- Sealing joints without or with low movement in plasterboard or drywall systems.

NORMS / ATESTS / CERTIFICATES

The product meets requirements of:

- EN 13963:2014

TECHNICAL DATA

Appearance	Value
Thixotropic paste	+
Colour	Value
White	+
Parameter	Value
Density at +20°C [g/cm ³]	0,50 ± 0,02

METHOD OF USE

Prior to application, read safety instruction presented in MSDS.

Surface preparation

- Surfaces must be clean, free from dust, mud, grease.

Product preparation

- Product ready for use.

Application

- Apply product directly with the nozzle of the cartridge.
- Smooth the surface with a moistened spatula to obtain a good smooth finish.
- Once the product is dry it can be sanded or painted if necessary.
- Due to the wide variety of paints available, a compatibility test is recommended prior to paint application.

Works after completion of application

- Cleaning work tools can be done with warm water when the product is fresh.

Remarks / restriction

- Once dry the product can be painted.

ADDITIONAL INFORMATION

The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena FM S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent. Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically.

TRANSPORT / STORAGE

Shelf life: 12 months.

Store in its original closed package.

Store a recommended temperature between 5 and 25°C.

CATALOGUE DATA

Nominal capacity / volume / size	Colour	Number of pieces per collective package	Index	EAN Code
280 ml	white	12	10041716	5902120176489
280 ml	white	12	10041704	5902120175772
300 ml	white	12	10043380	5902120011513



SAFETY AND HEALTH PRECAUTIONS

According to current legislation, this product is exempt from any indication of risk or safety in its handling or storage.

For more information request Safety Data Sheet.