

TYTAN PROFESSIONAL Acrylic Silicone

Acrylic silicone (based on silanised acrylic) is an excellent sealant giving a flexible and paintable joint. It contains fungicides to prevent mould formation and development. After hardening, it forms a smooth and easy to clean surface with high resistance to dust. It is characterized by very good adhesion to most surfaces, even wet ones. It does not require a primer. After curing it forms a smooth and easy to clean surface. It is practically odourless.



BENEFITS

- odourless and chemically neutral
- possibility of applying multiple layers after curing
- aesthetic, shiny joint
- high flexibility after curing

RECOMMENDED USES

- sealing baths, hand basins, showers, sinks and other sanitary facilities and other water supply equipment
- filling joints around wooden frames, at laths, window sills
- filling gaps between the baseboard and wall
- grouting of corners of walls and ceilings
- connecting of drywalls (including grouting of corners)

NORMS / ATESTS / CERTIFICATES

The product meets requirements of:

- EN 15651-3:2012 S

TECHNICAL DATA

Uncured - tested at 23°C and 50% relative humidity	Value
Density (ISO 2811-1) [g/ml]	1,32 - 1,34
Skin formation time [min]	20 - 25
Curing rate [mm/24h]	1,0 - 1,5
Flow from vertical surfaces [+50°C] (ISO 7390) [mm]	0 - 3
Cured - tested after 4 weeks at 23°C and 50% relative humidity	Value
Module at 100% elongation (ISO 37) [MPa]	0,35 - 0,45
Movement accommodation (ISO 9047) [%]	12,5
Elongation at break (ISO 37) [%]	750 - 850
Elongation at break (ISO 8339) [%]	100 - 150
Elastic recovery (ISO 7389) [%]	25 - 35
Shore A hardness (ISO 868)	25 - 35
Temperature resistance [°C]	-20 - +80
Adhesion to surface	Value
Concrete	+/-
Galvanized sheet	+/-
Ceramic tile	+/-
Lacquered wood	+
PS (polystyrene)	+/-
PC (polycarbonate)	+/-
Brick	+

Plaster/Drywall	+
Cork	+
Foamed PS (styrofoam)	+
Raw wood (pine)	+
Hard PVC (polyvinyl chloride)	+
Heterogeneous PVC floor covering	+
Colour	Value
White	+
Grey	+
Conditions of application	Value
Surface temperature [°C]	+5 - +40
Container temperature [°C]	+5 - +25
Application temperature [°C]	+5 - +40

METHOD OF USE

Prior to application, read safety instruction presented in MSDS.

Surface preparation

- To avoid dirtiness around the gap and to maintain equal line use adhesive tapes which should be removed immediately after finishing sealing.
- Sealant does not require using primer on most surfaces but on some specific surfaces may have to use it to improve adhesion, that in all cases it is worth performing an adhesiveness test on the used surface.
- Bonding surfaces must be clean, dry (not frosted) free of dust, rust, old loose material, oil, grease, paint and other dirt which reduces the adhesion of the sealant.

Product preparation

- Prior to application, the product should be conditioned at room temperature.

Application

- Cut off the top of the threaded adapter. Screw the nozzle tip on and cut off at a 45° angle, with the diameter equal to the gap width.

- Cut off the top of the foil. Screw the nozzle tip on and cut off at a 45° angle, with the diameter equal to the gap width.
- Squeeze sealant by mechanical or pneumatic gun.
- Treatment make at the time of workability given in the technical data table.
- Applied sealant should be smoothed immediately with a spatula soaked in water for best result.
- Remove masking tape before skin will form.
- Joint should be allowed to fully cure.

Works after completion of application

- Clean while uncured with water or water and soap.
- After curing, remove from hands with water and soap; from tools remove mechanically.
- Freshly applied sealant should be protected from rain and direct action of water for minimum 6 hours.
- DO NOT WASH HANDS WITH SOLVENTS.

Remarks / restriction

- Sealant should not be used on bituminous surfaces, partially vulcanized rubber, chloroprene or other construction materials that bleed oils, plasticizers or solvents.
- Sealant is not intended for sealing joints of natural stone, such as granite, sandstone, marble, etc.
- Sealant is not recommended for joints that are permanently under water, because it can cause physical changes.
- Not suitable for bonding aquariums and terrariums.
- Sealant is not intended for applications involving structural glazing.
- It is not suitable for direct contact with food and medical uses. Sealant was not duly tested and it is not suitable for medical and pharmaceutical applications.
- Before painting it is recommended to conduct a trial test, especially in a case of solvent-based paints.
- Do not apply on PE, PP - no adhesion.
- Do not apply on sensitive metal surfaces for example copper and its alloys and silver steel of mirrors.

ADDITIONAL INFORMATION

All given parameters are based on laboratory tests compliant with internal manufacturer's standards and strongly depend on product hardening conditions (c.a., ambient, surface temperature, quality of used equipment and skills of person applying the product).

TRANSPORT / STORAGE

Warranted shelf life is 24 months from the manufacturing date when stored in unopened, original package at temperature from +5 °C to +25 °C in a dry place protected from freezing.

Product can be transported at low temperatures up to -5 °C for up to 2 weeks, before using the product should be conditioned for 24 hours at +23 °C.

Precautions should be taken when the product after thawing out is frosted again - is resistant to 1 cycles of freezing/thawing out.

CATALOGUE DATA

Nominal capacity / volume / size	Colour	Number of pieces per collective package	Index	EAN Code
280 ml	white	12	10041532	5902120175475

SAFETY AND HEALTH PRECAUTIONS

For detailed information find Material Safety Data Sheet available at producer upon request.

All written or oral information, recommendations and instructions are given according to our best knowledge, tests and experience, in good faith and in compliance with manufacturer's principles. Each user of this material will make sure in every possible way, including verification of the final product in proper conditions, about suitability of the supplied materials for their intended purposes. The manufacturer is not liable for any losses incurred due to inaccurate or erroneous application of the manufacturer's materials.