

# NO NAME OSAKRYL Universal Carpet Adhesive

One-component adhesive free of organic solvents, intended for finishing works in the construction industry, primarily for bonding floor coverings to various types of absorbent substrates.



## BENEFITS

- Organic solvent-free
- durable initial tack
- good adhesion
- good application
- for universal use

## RECOMMENDED USES

- gluing carpet, PVC and floor coverings on a felt backing
- gluing other finishing materials (e.g. cork, mineral wool and polystyrene boards)

## TABLES

### TECHNICAL DATA

Coating appearance	not applicable
Viscosity	60000 +/- 20000 mPas 20 rpm, disk 7
Density	1,7 +/- 0,1
pH	8-9
The number of layers	not applicable
Application of the second layer	not applicable
Total drying time	72 h
Efficiency	1,7 kg/m <sup>2</sup> 1mm
Tools	float, putty
Shelf life	2 years
The VOC limit	not applicable
Colors	beige
Packaging	1 kg - plastic bucket; 4kg, 7kg, 14kg, 20kg - plastic bucket

### TECHNICAL DATA

Other	Value
Viscosity [mPas 20 rpm, disc 7]	60000 +/- 20000
Density	1,7 +/- 0,1
pH	8-9
Total drying time [h]	72
Efficiency [kg/m <sup>2</sup> 1mm]	1,7
Expiration date [months]	48
VOC content	ND
Beige	+
Packaging - pails [kg]	1 ; 4 ; 7 ; 14 ; 20

## METHOD OF USE

Before use, carefully read the directions on the packaging and act accordingly. Before starting the application, read the safety instructions in the MSDS.

### Surface preparation

- Clean the substrate, remove dust, dry and level it.

### Product preparation

- Before use, season the glue and glued elements for one day in the room where they will be used.
- Before use, the product should be mixed thoroughly.

### Application

- The adhesive can be applied on substrates with the following moisture content: cement substrate - max 3%; anhydrite or gypsum substrate - max 0.5%.
- Gluing should be carried out in dry rooms with a temperature not lower than 10°C.
- Apply the adhesive with a notched spatula so that the entire surface is moist.
- After approx. 10 min. Lay the floor covering and press it firmly against the base in order to remove air bubbles.
- The floor covering should adhere exactly to the substrate.
- The joint reaches its full strength after approx. 3 days. Until then, do not use the surface and avoid getting it wet.

### Works after completion of application

- Do not dispose of with household waste, do not pour into sewage system.
- Waste should always be managed in accordance with the applicable national regulations on waste.

## TRANSPORT / STORAGE

Storage temperature from 5°C to 30°C.

Store in a place inaccessible to children.

For detailed transport information, please refer to the Safety Data Sheet.

Packaging: Plastic pails 1kg, 4kg, 7kg, 14kg, 20kg

## CATALOGUE DATA

Nominal capacity / volume / size	Colour	Number of pieces per collective package	Index	EAN Code
1 kg	white	6	10002902	5903518039508
14 kg	white	nd	10002903	5903518042041
20 kg	white	nd	10002904	5903518039539
4 kg	white	nd	10002905	5903518039515
7 kg	white	nd	10002906	5903518039522

## SAFETY AND HEALTH PRECAUTIONS

Protect eyes and skin, in case of contact, rinse immediately with water.

Possible dirt should be removed without waiting for it to dry.

All written or oral information, recommendations and instructions are given according to our best knowledge, tests and experience, in good faith and in compliance with manufacturer's principles. Each user of this material will make sure in every possible way, including verification of the final product in proper conditions, about suitability of the supplied materials for their intended purposes. The manufacturer is not liable for any losses incurred due to inaccurate or erroneous application of the manufacturer's materials.