

# TYTAN PROFESSIONAL Flexi Gum 400 ml black

10045047, 10040530, 10040911, 10046252

TYTAN PROFESSIONAL FLEXI GUM is a quick and easy way to flexibly seal leaks and cracks on most construction surfaces. The repair aerosol sealant creates a tight film, preventing the penetration of moisture, rust and corrosion.

## BENEFITS

- Flexible, sealing coating, prevents penetration of moisture and corrosion
- Fills leaks and cracks
- does not run off vertical surfaces
- Paintable - forms a smooth film that can be covered with latex or oil-based paints
- easy to use
- Quick-drying
- indoor and outdoor

## RECOMMENDED USES

- Concrete, bituminous and asphaltic surfaces
- PVC and wooden surfaces
- Metal surfaces, including galvanised and aluminium surfaces
- Ceramic surfaces

## TECHNICAL DATA

Parameter	Value
Appearance of the coating matt	+
Dust dry [min]	20-30
Full cure time [h]	72
Approximate capacity (70 µm)	0,8m <sup>2</sup> /400ml
Colour	Value

1/3

Black	+
Transparent	+
Conditions of application	Value
Application temperature [°C]	+5- +25
Can temperature [°C]	+ 5- +25

## METHOD OF USE

Before use, carefully read the directions on the packaging and act accordingly.

### Surface preparation

- The surface should be clean, dry and free of grease.

### Product preparation

- Shake the can vigorously for about 1 minute.

### Application

- Protect surfaces exposed to dirt.
- Perform a test spray.
- During application hold the can approx. 8-20 cm from the surface to be protected.
- It is recommended to apply two layers of the product. The first layer should be thinner.
- After approx. 15-30 min, apply a second, thicker coat.

### Works after completion of application

- When finished, turn the can upside down, press the nozzle and hold for 2-3 sec to clear the valve.

### Remarks / restriction

- In the case of larger gaps, it is recommended to apply the preparation topically, in the amount necessary to fill the cavity.

## ADDITIONAL INFORMATION

With the publication of this Technical Data Sheet, previous editions are no longer valid.



## TRANSPORT / STORAGE

Warranted shelf life is 10 years from the manufacturing date when stored in unopened, original package at temperatures from 10°C to 25°C in a dry place protected from freezing and excessive heat.

## SAFETY AND HEALTH PRECAUTIONS

All written or oral information, recommendations and instructions are given according to our best knowledge, tests and experience, in good faith and in compliance with manufacturer's principles. Each user of this material will make sure in every possible way, including verification of the final product in proper conditions, about suitability of the supplied materials for their intended purposes. The manufacturer is not liable for any losses incurred due to inaccurate or erroneous application of the manufacturer's materials.

The product is inflammable. All works should be carried out in well-ventilated area away from ignition sources. Do not smoke. The adhesive should be stored in accordance with the rules of storage of inflammable substances. Detailed information is included in the Safety Data Sheet (SDS).