

# TYTAN PROFESSIONAL High-Temperature Silicone

## 280 ml red

SEA-SILAHTMP3-TP-35-ml-280-140



Liquid silicone gasket with an acidic (acetate) curing system. Replaces traditional car gaskets (e.g. rubber ones). After curing, it forms a durable and flexible joint with resistance from -50°C up to +315°C and to chemicals (greases, oils). It forms a durable and non-shrinking joint, resistant to UV radiation. It is gas- and water-resistant. It has excellent adhesion to surfaces such as: glass, ceramics, wood and aluminium.

### BENEFITS

- high temperature resistance
- good adhesion to many smooth building materials
- high resistance to UV radiation
- fast curing rate
- low shrinkage
- permanent flexible joint
- excellent chemical resistance

### INTENDED USE

- sealing cylinder heads of car engines
- sealing of refrigeration, ventilation, heating and air conditioning systems
- sealing and connecting in motors, powertrains, radiators and motor pumps
- bonding and sealing in places exposed to high temperatures

## NORMS / ATESTS / CERTIFICATES

The product meets requirements of:

- ISO 11600 : 2004, F&G, 20HM

## METHOD OF USE

Prior to application, read safety instruction presented in MSDS.

### Surface preparation

- Bonding surfaces must be clean, dry (not frosted) free of dust, rust, old loose material, oil, grease, paint and other dirt which reduces the adhesion of the sealant.
- Surfaces best degrease with acetone or ethanol (glass, glaze, metal) or detergent (synthetic materials).
- To avoid dirtiness around the gap and to maintain equal line use adhesive tapes which should be removed immediately after finishing sealing.
- Sealant does not require using primer on most surfaces but on some specific surfaces may have to use it to improve adhesion.
- Joint width should be as to be able to carry movement in range calculated for sealant in question (movement accommodation).

### Product preparation

- Prior to application, the product should be conditioned at room temperature.

### Application

- Cut off the top of the threaded adapter. Screw the nozzle tip on and cut off at a 45° angle, with the diameter equal to the gap width.
- Cut off the top of the foil. Screw the nozzle tip on and cut off at a 45° angle, with the diameter equal to the gap width.
- Squeeze sealant by mechanical or pneumatic gun.
- Treatment make at the time of workability given in the technical data table.
- Applied sealant should be smoothed immediately with a spatula soaked in soapy water for best result.
- Remove masking tape before skin will form.
- Joint should be allowed to fully cure.

### Works after completion of application

- Uncured product should be removed from hands, tools and dirty surfaces with paper towel.



- After curing, remove from hands with water and soap; from tools remove mechanically. or using agent for removing silicones - Silicone Remover.
- DO NOT WASH HANDS WITH SOLVENTS.

## Remarks / restriction

- Do not apply on wet surfaces.
- Due to the acetic acid released during curing, acid silicone is not recommended for use on calcareous substrates such as concrete, plaster, brick.
- Sealant is not intended for sealing joints of natural stone, such as granite, sandstone, marble, etc.
- Sealant should not be used on bituminous surfaces, partially vulcanized rubber, chloroprene or other construction materials that bleed oils, plasticizers or solvents.
- Do not apply on sensitive metal surfaces for example copper and its alloys and silver steel of mirrors.
- Sealant is not recommended for joints that are permanently under water, because it can cause physical changes.
- Do not use in totally confined spaces where it is not exposed to atmospheric moisture, because the sealant requires atmospheric moisture for cure.
- Sealant is not intended for applications involving structural glazing.
- Silicone should not be painted.
- It is not suitable for direct contact with food and medical uses. Sealant was not duly tested and it is not suitable for medical and pharmaceutical applications.
- Do not apply on PE, PP - no adhesion.
- Not suitable for bonding mirrors.

## REMARKS / RESTRICTION

All given parameters are based on laboratory tests compliant with internal manufacturer's standards and strongly depend on product hardening conditions (c.a., ambient, surface temperature, quality of used equipment and skills of person applying the product).

## TRANSPORT / STORAGE

Warranted shelf life is 24 months from the manufacturing date when stored in unopened, original package at temperature from +0 °C to +25 °C in a dry place protected from freezing.

## SAFETY AND HEALTH PRECAUTIONS

For detailed information find Material Safety Data Sheet available at producer upon request.

All written or oral information, recommendations and instructions are given according to our best knowledge, tests and experience, in good faith and in compliance with manufacturer's principles. Each user of this material will make sure in every possible way, including verification of the final product in proper conditions, about suitability of the supplied materials for their intended purposes. The manufacturer is not liable for any losses incurred due to inaccurate or erroneous application of the manufacturer's materials.