

# TYTAN PROFESSIONAL Mounting Adhesive SBS 600 ml yellow



One-component solvent-based adhesive based on styrene-butadiene rubber (SBS) for renovation and finishing works in the building industry. It has excellent adhesion to most substrates and increased joint strength.



## BENEFITS

- fast and durable initial tack
- flexible joint
- high final strength
- excellent adhesion
- moisture resistant

## RECOMMENDED USES

- For bonding a wide range of building materials to most common surfaces such as concrete, plaster, particleboard, wood, gypsum board, brick
- Bonding of wall slats, plinths, thresholds, panels, ceramic tiles
- Bonding decorative elements made of wood, plaster, cork, chipboard, metal, stone, polystyrene
- Bonding of mineral and glass wool
- Sticking of carpets and PVC floor coverings

## TECHNICAL DATA

Uncured	Value
Base: synthetic rubber in organic solvents	+
Working time (depending on ambient conditions and subfloor properties) [min]	10 - 15
Full cure time [h]	>48
Consumption [g/m <sup>2</sup> ]	300 - 500

1/3

Update date: 20.08.2025

Cured	Value
Temperature resistance [°C]	-20 - +60
Conditions of application	Value
Optimal bonding temperature [°C]	+15 - +20
Application temperature [°C]	+10 - +30
Optimal relative air humidity [%]	60

## METHOD OF USE

Prior to application, read safety instruction presented in MSDS.

### Surface preparation

- Bonded surfaces must be level, dry, free from contaminations and substances hindering adhesion.

### Product preparation

- Apply the product using a mechanical or pneumatic squeezer.

### Application

- Apply adhesive in spots or strips on the surface or bonded material.
- Immediately join the surfaces firmly together with a little twist motion, disconnect them, wait 3-5 minutes and press again strongly and evenly.
- Element's position can be easily corrected without disconnecting for 2-3 minutes after connection.

### Works after completion of application

- Cleaning: before curing acetone or mineral spirits, after curing mechanically.
- DO NOT WASH HANDS WITH SOLVENTS.

### Remarks / restriction

- Adhesion tests prior to application of the adhesive are recommended.
- Avoid contact with water until the adhesive is fully cured.
- Not recommended for PE, PP, Teflon, surfaces permanently wet.
- Not suitable for solvent sensitive surfaces.

## TRANSPORT / STORAGE

Expiry date and batch number on packaging.

Store in the original packaging in a dry place, protected from frost and overheating, at a temperature of +5°C to +25°C.

## SAFETY AND HEALTH PRECAUTIONS

All written or oral information, recommendations and instructions are given according to our best knowledge, tests and experience, in good faith and in compliance with manufacturer's principles. Each user of this material will make sure in every possible way, including verification of the final product in proper conditions, about suitability of the supplied materials for their intended purposes. The manufacturer is not liable for any losses incurred due to inaccurate or erroneous application of the manufacturer's materials.