

TYTAN PROFESSIONAL PU Foam Cleaner 500 ml



10052602

A multifunctional, reusable agent for removing uncured polyurethane foams and adhesives. Indispensable for cleaning valves, nozzles, containers and application-related tools for adhesives and polyurethane foams. Perfect for degreasing surfaces before applying silicones, adhesives, foams and other construction chemicals.

BENEFITS

- the product perfectly degreases metal surfaces, e.g., before the application of silicones and polyurethane
- multi-use possibility
- can be used with any gun type

RECOMMENDED USES

Removing uncured fresh polyurethane foams and adhesives

Cleaning of spray can valves, PU-foam gun applicators

Degreasing of surfaces

TECHNICAL DATA

Parameter (+23°C/50% RH)	Value
Can size [ml]	650
Nominal value [ml]	500
Consistency: liquid	+
Conditions of application	Value
Can / applicator temperature (optimal +20°C) [°C]	+5 - +35
Ambient/surface temperature [°C]	+5 - +35

1/3

Update date: 17.10.2025

ТОВ «СЕЛЕНА УКРАЇНА»

03039 Україна, м. Київ, проспект Валерія Лобановського, буд 119, літера «Х», оф. 33,
тел. +38 (044) 364 99 27, +38 (044) 364 99 28, office.ua@selenacom, www.tytan.ua



Colour	Value
Transparent	+

METHOD OF USE

Prior to application, read safety instruction presented at the end of TDS and in MSDS.

Application

- Manual application - fix the enclosed spraying nozzle onto Cleaner valve. Spray the can valve and fresh stains of PU foam or adhesive with the cleaner. Remove stains with a dry cloth.
- Gun cleaning — unscrew the foam/glue can from the gun. Press the gun trigger to remove any residual foam/glue. Next, place the plastic tube supplied with the dispensing gun packaging on the dispensing gun outlet to avoid the formation of mist containing the cleaning agent and gun residues during cleaning. Screw the gun onto the cleaning agent container. Press the gun trigger several times. Repeat this procedure until the gun is completely clean of foam/adhesive.

Remarks / restriction

- Dissolving only uncured one-component PU-foams and adhesives.
- Cleaner has a destructive effect on the polystyrene, PVC and some other plastics, before use, test the cleaner on a given surface.

TRANSPORT / STORAGE

Warranted shelf life is 36 months from the manufacturing date when stored in a dry and cool place in original cans away from fire source. Storage temperature: from +5°C to +30°C. It is not allowed to store cans of Cleaner in temperature exceeding +50°C.

Do not store in the passenger compartment. Transported only in the trunk.

Detailed transport information is included in the Material Safety Data Sheet (MSDS).

CATALOGUE DATA

Nominal capacity / volume / size	Colour	Number of pieces per collective package	Index	EAN Code
500 ml	N/A	12	10052602	5902120257843

SAFETY AND HEALTH PRECAUTIONS

The information contained herein is offered in good faith based on Producer's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Producer's products are fully satisfactory for your specific applications. Producer's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Producer specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Producer disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.