

1. Unique identification code of the product-type:

## Tytan Professional FIX2 Flex Adhesive-Sealant



2. **Type, batch or serial number** or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. **Intended use or uses** of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

### EN 15651-1:2012 Type F-EXT-INT-CC Class 20HM

non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face (intended for use in cold climates)

### EN 15651-3:2012 Type S Class XS 2

sealant used for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water

### EN 15651-4:2012 Type PW-EXT-INT-CC Class 20HM

cold applied non-structural elastic sealant used for movement joints in floors in building construction for interior and exterior use (intended for use in cold climates)

4. Name, registered trade name or registered trade mark and contact address of the **manufacturer** as required pursuant to Article 11(5):

SELENA FM S.A.  
 Legnicka 48A  
 54-202 Wrocław  
 Poland

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. **System or systems of assessment** and verification of constancy of performance of the construction product as set out in Annex V:

system 3 for type of testing  
 system 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a **harmonised standard**:

The notified body Tecnia, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

The notified body Tecnia, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: classification report

8. In case of the declaration of performance concerning a construction product for which a **European Technical Assessment** has been issued:

not relevant

9. Declared performance

### EN 15651-1:2012 Type F-EXT-INT-CC

Conditioning: Method A

Substrate: mortar, M2 with primer "Primer-C27"

| Essential characteristics                                                                                                           | Performance                   | Test Standard                                       | Harmonised technical specification |
|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|-----------------------------------------------------|------------------------------------|
| Reaction to fire                                                                                                                    | Class E                       | EN 13501-1:2007+A1                                  | EN 15651-1:2012                    |
| Release of chemicals dangerous to the environment and health                                                                        | See product safety data sheet | EN 15651-1:2012; 4.5                                | EN 15651-1:2012                    |
| Water tightness and air tightness:                                                                                                  |                               |                                                     |                                    |
| Resistance to flow                                                                                                                  | ≤ 3 mm                        | modified EN ISO 7390                                | EN 15651-1:2012                    |
| Loss of volume                                                                                                                      | ≤ 10 %                        | EN ISO 10563                                        | EN 15651-1:2012                    |
| Tensile properties (i.e. elongation):<br>- after immersion in water at (23 °C)                                                      | NPD                           | EN ISO 10591                                        | EN 15651-1:2012                    |
| Tensile properties (i.e. elongation):<br>- at maintained extension after water immersion                                            | NF                            | EN ISO 10590                                        | EN 15651-1:2012                    |
| Tensile properties (i.e. secant modulus):<br>- for non-structural low modulus sealants used in joints in cold climate areas (-30°C) | NPD                           | modified EN ISO 8339                                | EN 15651-1:2012                    |
| Tensile properties (i.e. at maintained extension):<br>- for non-structural sealants used in joints in cold climate areas (-30°C)    | NF                            | modified EN ISO 8340                                | EN 15651-1:2012                    |
| Durability                                                                                                                          | Pass                          | EN ISO 8339, EN ISO 8340, EN ISO 9047, EN ISO 10590 | EN 15651-1:2012                    |

## EN 15651-3:2012 Type S

Conditioning: Method A

Substrate: glass without primer

| Essential characteristics                                                                | Performance                   | Test Standard                | Harmonised technical specification |
|------------------------------------------------------------------------------------------|-------------------------------|------------------------------|------------------------------------|
| Reaction to fire                                                                         | Class E                       | EN 13501-1:2007+A1           | EN 15651-3:2012                    |
| Release of chemicals dangerous to the environment and health                             | See product safety data sheet | EN 15651-1:2012; 4.5         | EN 15651-3:2012                    |
| Water tightness and air tightness:                                                       |                               |                              |                                    |
| Resistance to flow                                                                       | ≤ 3 mm                        | modified EN ISO 7390         | EN 15651-3:2012                    |
| Loss of volume                                                                           | ≤ 20 %                        | EN ISO 10563                 | EN 15651-3:2012                    |
| Tensile properties (i.e. elongation):<br>- after immersion in water at (23 °C)           | NPD                           | EN ISO 10591                 | EN 15651-3:2012                    |
| Tensile properties (i.e. elongation):<br>- at maintained extension after water immersion | NF                            | EN ISO 10590                 | EN 15651-3:2012                    |
| Microbiological growth                                                                   | 2                             | EN ISO 846:1997, procedure B | EN 15651-3:2012                    |

|            |      |                                                    |                 |
|------------|------|----------------------------------------------------|-----------------|
| Durability | Pass | EN ISO 8340, EN ISO 846, EN ISO 9047, EN ISO 10590 | EN 15651-3:2012 |
|------------|------|----------------------------------------------------|-----------------|

**EN 15651-4:2012 Type PW-EXT-INT-CC**  
Conditioning: Method A  
Substrate: mortar, M2 with primer "Primer-C27"

| Essential characteristics                                                               | Performance                   | Test Standard                                       | Harmonised technical specification |
|-----------------------------------------------------------------------------------------|-------------------------------|-----------------------------------------------------|------------------------------------|
| Reaction to fire                                                                        | Class E                       | EN 13501-1:2007+A1                                  | EN 15651-4:2012                    |
| Release of chemicals dangerous to the environment and health                            | See product safety data sheet | EN 15651-1:2012; 4.5                                | EN 15651-4:2012                    |
| Water tightness and air tightness:                                                      |                               |                                                     |                                    |
| Tensile properties at maintained extension                                              | NF                            | EN ISO 8340                                         | EN 15651-4:2012                    |
| Loss of volume                                                                          | ≤ 10 %                        | EN ISO 10563                                        | EN 15651-4:2012                    |
| Tear resistance                                                                         | NF                            | modified EN ISO 8340                                | EN 15651-4:2012                    |
| Adhesion/cohesion properties at maintained extension after 28 days water immersion      | NF                            | modified EN ISO 10590                               | EN 15651-4:2012                    |
| Adhesion/cohesion properties at maintained extension after 28 days salt water immersion | NF                            | modified EN ISO 10590                               | EN 15651-4:2012                    |
| Tensile properties (i.e. secant modulus) at (-30 ± 2)°C for cold climate areas          | NPD                           | modified EN ISO 8339                                | EN 15651-4:2012                    |
| Tensile properties at maintained extension at (-30 ± 2)°C for cold climate areas        | NF                            | EN ISO 8340                                         | EN 15651-4:2012                    |
| Durability                                                                              | Pass                          | EN ISO 8339, EN ISO 8340, EN ISO 9047, EN ISO 10590 | EN 15651-4:2012                    |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the  
manufacturer by:

Ewa Topór  
(R&D Certification Coordinator)



14.02.2025, Wrocław

## Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance