

WINDOW & DOOR

INSULATING FOAM SEALANT



LOW
EXPANSION

NO-BOW
TECHNOLOGY



- ▶ Resists water and prevents mold problems
- ▶ More R-value per inch
- ▶ Dry & wet climate

WINDOW & DOOR INSULATING FOAM SEALANT



ASTM E84 | AAMA 812-19 | UL 723

TYTAN Professional Window & Door Insulating Foam Sealant is AAMA/FGIA approved and uses innovative no-bow technology to create a water and airtight seal!

HOW IT WORKS

TYTAN Window & Door Insulating Foam Sealant provides more R-value per inch in combination with superior yield, allowing installers to install more windows & doors. The increased R-value reduces energy consumption and contributes to LEED's energy-saving standards while being environmentally friendly, containing no CFC's or HCFC's.

- **Minimal expansion technology**
- **More R-value per inch**
- **Energy saving standards**



Formulated for sealing:

- **Windows**
- **Door frames**
- **Spaces, cracks, gaps, etc.**

RECOMMENDED FOR USE WITH TYTAN PRO APPLICATOR

TYTAN's Pro applicator allows everyday professional users to install foam sealants quickly and reliably. It is made with a heavy duty metal construction design and teflon-coated basket that allows exterior mechanical removal of cured foam.



TYTAN Professional is a brand of the Selena Group, a global leader and distributor of construction chemicals and one of the four largest producers of polyurethane foam in the world. Selena was founded in 1992 in Wroclaw, Poland. Visit [TYTAN.com/us](https://www.tytan.com/us) to learn more.