Revision nr. 1 Dated 13/05/2021 First compilation Printed on 14/05/2021 Page n. 1/17



Safety Data Sheet According to Annex II to REACH - Regulation 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

U200-U0CW-500K-Q9PH UFI:

Product name TYTAN ANCORANTE CHIMICO EV I COMP. B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Chemical anchor

Identified Uses Industrial Professional Consumer Chemical anchor

1.3. Details of the supplier of the safety data sheet

Name

Full address e-mail address of the competent person

Via del Teroldego, 6 38016- MEZZOCORONA (TN)

Tel: +39 049 767 336 - Fax: +39 049 884 332

E-mail: servizio.clienti@selena.com

www.tytan.com/it

UNIFLEX SRL

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation. Skin sensitization, category 1 May cause an allergic skin reaction. H317 Hazardous to the aquatic environment, chronic toxicity, H412 Harmful to aquatic life with long lasting effects. category 3

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 2/17



2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P280 Wear protective gloves / eye protection / face protection.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P273 Avoid release to the environment.

Contains: dibenzoyl peroxide

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration >= 0.1%.

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 3/17



SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

dibenzoyl peroxide

CAS 94-36-0 $10 \le x < 21$ Org. Perox B H241, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1

H400 M=10, Aquatic Chronic 1 H410 M=10, Classification note according to

Annex VI to the CLP Regulation: T

EC 202-327-6

INDEX 617-008-00-0

REACH Reg. 01-2119511472-50-

XXXX

ETHANEDIOL

CAS 107-21-1 9 ≤ x < 10 Acute Tox. 4 H302, STOT RE 2 H373

EC 203-473-3 STA Oral: 500 mg/kg

INDEX 603-027-00-1

REACH Reg. 01-2119456816-28-

XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Ethylene glycol

Acute dose-dependent effects.

Skin: irritation

Nervous system: depression, convulsions, coma if ingested

Eyes: irritation

Upper airways: irritation

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 4/17



Lungs: irritation

Digestive system: nausea, vomiting, abdominal colic if ingested

Urogenital system: kidney damage

Chronic effects.

Nervous system: depression, ocular nystagmus

Eyes: irritation Lungs: irritation

4.3. Indication of any immediate medical attention and special treatment needed

Ethylene alvcol

Useful antidote: administer Ethanol 750 mg / kg, Fomepizole in case of ingestion

Useful urgent medical intervention

There is a first phase from 30 'to 12 hours with symptoms affecting the central nervous system.

A second phase between 12-24 hours with symptoms affecting the cardiovascular system.

Kidney damage between 24-72 hours.

Between 6-14 days degeneration of the central nervous system.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 5/17

contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



6.2. Environmental precaution

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κυδύνους που συμδέρνται με την έκθεση σε καρκιγονόνους ή

μεταλλαξιγόνους παράγοντες κατά την εργασία``»

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 6/17

HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

dibenzoyl peroxide								
Predicted no-effect concentration	on - PNEC							
Normal value in fresh water				20	ng/	L		
Normal value in marine water				2	ng/	L		
Normal value for fresh water se	ediment			12,7	ug/	kg		
Normal value for marine water	sediment			1,27	ug/	kg		
Normal value of STP microorg	anisms			350	ug/	L		
Health - Derived no-effec	t level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic

 Systemic
 systemic
 systemic

 Oral
 2 mg/kg bw/d
 39 mg/m3

 Inhalation
 39 mg/m3

 Skin
 0,034 mg/kg bw/d
 13,3 mg/kg bw/d

ETHANEDIOL							
Threshold Limit Val							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	52	20	104	40	SKIN	
TLV	CZE	50	19,7	100	39,4	SKIN	
AGW	DEU	26	10	52	20	SKIN	
MAK	DEU	26	10	52	20	SKIN	
VLA	ESP	52	20	104	40	SKIN	
VLEP	FRA	52	20	104	40	SKIN	
TLV	GRC	125	50	125	50		
AK	HUN	52		104		SKIN	
VLEP	ITA	52	20	104	40	SKIN	
TGG	NLD	52		104		SKIN	
VLE	PRT	52	20	104	40	SKIN	
NDS/NDSCh	POL	15		50		SKIN	
NPEL	SVK	52	20	104	40	SKIN	
WEL	GBR	52	20	104	40	SKIN	

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 7/17

OEL	EU	52	20	104	40	SKIN	
TLV-ACGIH			25		50		
TLV-ACGIH				10		INHAL	

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374). Nitrile gloves. Viton gloves. EN 374 Recommended thickness of material> 0.4 mm. Breakthrough time of glove material> 8 hours.

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

None required, unless indicated otherwise in the chemical risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	Pasty solid	
Colour	grey	
Odour	barely noticeable	
Odour threshold	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not applicable	

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 8/17

Flammability Not available Lower explosive limit Not available Upper explosive limit Not available Flash point Not applicable Auto-ignition temperature Not available Decomposition temperature Not available Not available рΗ Kinematic viscosity Not available Dynamic viscosity Altamente viscoso Solubility insoluble in water Partition coefficient: n-octanol/water Not available Vapour pressure Not available Density and/or relative density 1,45 Relative vapour density Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

the product has been tested by the German Authority "Bundesanstalt für Materialforschung und - prüfung (BAM)" The value resulting from the formula given in paragraph 2.15.2.1 of CLP regulation is under 1%. Therefore does not require classification as H241.

9.2.2. Other safety characteristics

SADT = 50 C. The SADT (self accelerating decomposition temperature) is an experimentally determined temperature at which the product, in its conventional packaging will decompose in a selfaccelerating reaction. Solid suspension – classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

SECTION 10. Stability and reactivity

10.1. Reactivity

ETHANEDIOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable if stored in original containers at temperatures lower than the self accelerated decomposition temperature (SADT).

10.3. Possibility of hazardous reactions

ETHANEDIOL

Risk of explosion on contact with: perchloric acid.May react dangerously with: chlorosulphuric acid,sodium hydroxide,sulphuric acid,phosphorus pentasulphide,chromium (III) oxide,chromyl chloride,potassium perchlorate,potassium dichromate,sodium peroxide,aluminium.Forms explosive mixtures with: air.

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 9/17



10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. Avoid transferring into containers that may have been contaminated with other substances. Avoid storing close to inflammable or combustible products.

ETHANEDIOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the formation of explosive peroxides or other potentially hazardous substances.

ETHANEDIOL

May develop: hydroxyacetaldehyde,glyoxal,acetaldehyde,methane,carbon monoxide,hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 10/17



ETHANEDIOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

ì	124252	atia	effects
ı	ıntera	crive	enects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

>2000 mg/kg

Not classified (no significant component)

dibenzoyl peroxide

LD50 (Oral): 2000 mg/kg LC50 (Inhalation mists/powders): 24,3 mg/l/4h

ETHANEDIOL

LD50 (Oral): > 2000 mg/kg Rat

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Dermal): 9530 mg/kg Rabbit

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 11/17



GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

FTHANFDIOL

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Revision nr. 1 Dated 13/05/2021 First compilation Printed on 14/05/2021 Page n. 12/17



11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. 12.1. Toxicity

Mixture		
ALGAE (OECD TG 201)	72H EC50	> 60 mg / I
FISH (OECD TG 203)	96H LC50	> 100 mg / l
Daphnia magna (OECD TG 202)	48H EC50	> 10 mg/l
FISH (OECD TG 215)	28d NOEC	> 7 mg / l

dibenzoyl peroxide

LC50 - for Fish 0,0602 mg/l/96h EC50 - for Crustacea 0,11 mg/l/48h EC50 - for Algae / Aquatic Plants 0,0711 mg/l/72h

12.2. Persistence and degradability

ETHANEDIOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

ETHANEDIOL

Partition coefficient: n-octanol/water -1,36

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

Revision nr. 1 Dated 13/05/2021 First compilation
Printed on 14/05/2021 Page n. 13/17



SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Not applicable

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.	
Rejection code: 08 04 09 Packaging disposal: Directive (EU) 2018/852 on packaging and packaging waste. 165 ml cartridge PP RIC5, PP cap RIC5. 300 ml cartridge PP RPE-HD cap RIC5. 400-420ml nylon cartridge RIC7, PP cap RIC5. NB: The user's attention is drawn to the possible existence of regional or national regulations on disposal.	llCŧ
SECTION 14. Transport information	
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RIE the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.)), c
14.1. UN number or ID number	
Not applicable	
14.2. UN proper shipping name	
Mart and Parkla	
Not applicable	
14.3. Transport hazard class(es)	
Not applicable	
14.4. Packing group	

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 14/17



14.5.	Environmental	hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point 75

Regulation (EC) No. 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 15/17



None

Substances subject to the Stockholm Convention:

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Org. Perox B Organic peroxide, category B
Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2
Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H241 Heating may cause a fire or explosion.

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

Revision nr. 1 Dated 13/05/2021 First compilation Printed on 14/05/2021 Page n. 16/17

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)

- Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. 10th Edition
 Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Revision nr. 1
Dated 13/05/2021
First compilation
Printed on 14/05/2021
Page n. 17/17

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products. CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11. Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.